





Adjustable Single Post Anchor Assembly


Specification: The Adjustable Single Post Anchor Assembly is designed to prevent starting platform rocking. The assembly consists of a housing constructed of 4.00" (101.6 mm) x .25" (6.35mm) wall square stainless-steel tubing welded onto a 4.50" (114.3 mm) X .125" (3.18 mm) square flange. The anchor is provided with a grounding screw and a urethane liner that can be replaced when worn. The liner pairs with a stainless-steel adjustable wedge assembly. When tightened, the starting block is secured in the anchor. When loose, the starting block can be easily removed. A stainless-steel cap is provided to mount flush on the deck when the platform is removed. A cap removal key is provided with each anchor.

Shipping weight: 15 lbs. [1.81 kg.]



PRODUCT SPECIFICATIONS - DRAWING

Adjustable Single Post Anchor Assembly



ITEM NO.	PART NO.	DESCRIPTION
1	20-139P	PAVER ANCHOR HOUSING ASSEMBLY
2	4-602P	PAVER ANCHOR INSERT, URETHANE
3	20-240/20-241	MIDDLE WEDGE ASSEMBLY
4	4-113-1P	SINGLE POST ANCHOR CAP
5	5-215-1	ANCHOR CAP REMOVAL TOOL

Specification Number:	SRS-947		
Product Description:	Adjustable Single Post Anchor Assembly For Pool Deck Pavers		
S.R. Smith Part No.:	27-107P	Scale:	NTS
Revision:	A0	Date:	11/07/2018
Written By:	C. Redelfs	Date:	11/07/2018
Approved By:		Date:	
Page 2 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		



S.R. Smith, LLC
P.O. Box 400, 1017 SW Berg Parkway
Canby, Oregon 97013
Tel: (888) 677-7776 (503) 266-2231
Fax: (503) 266-4334
www.srsmith.com