



**Commercial Ring Handrails**



SIDE VIEW



FRONT VIEW

Specification Number:	<b>SRS-602</b>		
Product Description:	<b>Commercial Ring Handrails</b>		
S.R. Smith Part Number:	<b>CRH-100 to CRH-100B-MG</b>	Scale:	NTS
Revision:	A	Date:	05/29/03
Written By:	T. Weil	Date:	05/29/03
Approved By:	B. Bisceglia	Date:	05/30/03
Page 1 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		

**S.R. Smith, LLC**  
P.O. Box 400, 1017 SW Berg Parkway  
Canby, Oregon 97013  
Tel: (888) 677-7776 (503) 266-2231  
Fax: (503) 266-4334  
[www.srsmith.com](http://www.srsmith.com)



# S.R. Smith LLC Commercial Division

## Product Specifications - Written

**Product Name:** Commercial Ring Handrails

**Part Number:** CRH-100 to CRH-100B-MG

**General Notes:**

The **Commercial Ring Handrails** are a moderate height rail made of polished type 304 stainless steel. The handrails are of smaller diameter and the legs on either side mount in a single anchor socket. The Commercial Ring Handrails are to be used with recessed steps.

**Application:**

With proper anchoring, the Commercial Ring Handrail is suitable for use in conjunction with built-in steps on poured concrete, shotcrete, fiberglass, and vinyl commercial pools and spas as well as for other applications in most geographic areas.

**Specifications:**

- 1 **Handrails:** The handrails are made of 1-5/8" O.D. x .065 wall (41.3mm x 1.65) type 304 polished stainless steel and all bends are a nominal 6" (152.4mm) radius. Both ends of each handrail are drilled below deck level to allow for anchoring by reinforcing rods, if an anchor assembly is not desired.
- 2 **Escutcheon:** This escutcheon plate is 6.37" (162mm) in length and is made of chrome-plated bronze. The escutcheon is included with the anchor assembly.
- 3 **Anchor Assembly (Optional)** (p/n 34-305A or 34-306A, see spec sheet for SRS-915): The Double Anchor Socket Assembly is designed to accept 1-5/8" (41.3mm) dia. ring rails. It is intended for heavy-duty commercial use and secures fixtures by means of a wedge assembly. A jig plate is used to install railings at 20" (508mm) on center. p/n 34-305A is made of cast aluminum, and p/n 34-306A is made of cast brass.

**Additional Product Numbers and Shipping Weight:**

Model Number	Description	Shipping Weight
CRH-100	Commercial Ring Handrail (Pair)	14 lbs. (6.35kg)
CRH-100A	Commercial Ring Handrail (Pair) w/ Aluminum Anchor Assembly	24 lbs. (10.9kg)
CRH-100B	Commercial Ring Handrail (Pair) w/ Brass Anchor Assembly	27 lbs. (12.2kg)
CRH-100-MG	Marine Grade 316 Stainless Steel Commercial Ring Handrail (Pair)	14 lbs. (6.35kg)
CRH-100A-MG	Marine Grade 316 S.S. Commercial Ring Handrail (Pair) w/ Aluminum Anchor Assembly	24 lbs. (10.9kg)
CRH-100B-MG	Marine Grade 316 S.S. Commercial Ring Handrail (Pair) w/ Brass Anchor Assembly	27 lbs. (12.2kg)

Specification Number:	<b>SRS-602</b>	
Product Description:	<b>Commercial Ring Handrails</b>	
S.R. Smith Part Number:	<b>CRH-100 to CRH-100B-MG</b>	
Revision:	A	Date: 05/29/03
Written By:	T. Weil	Date: 05/29/03
Approved By:	B. Bisceglia	Date: 05/30/03
Page 2 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.	

**S.R. Smith, LLC**  
**P.O. Box 400, 1017 SW Berg Parkway**  
**Canby, Oregon 97013**  
**Tel: (888) 677-7776 (503) 266-2231**  
**Fax: (503) 266-4334**  
**www.srsmith.com**