


Pretzel Bend Handrails



MODEL NUMBER	DIMENSION A	DIMENSION B	TUBE DIMENSIONS
10169	8.50	17.00	1.90" O.D. X .109" WALL
10170	8.50	17.00	1.90" O.D. X .145" WALL
10171	10.63	26.00	1.90" O.D. X .109" WALL
10172	10.63	26.00	1.90" O.D. X .145" WALL
10173	10.63	30.00	1.90" O.D. X .109" WALL
10174	10.63	30.00	1.90" O.D. X .145" WALL

Specification Number:	SRS-612		
Product Description:	Pretzel Bend Handrails		
S.R. Smith Part Number:	10169 to 10174	Scale:	NTS
Revision:	A	Date:	07/29/03
Written By:	B. Svendsen	Date:	07/29/03
Approved By:	B. Bisceglia	Date:	07/29/03
Page 1 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		

S.R. Smith, LLC
P.O. Box 400, 1017 SW Berg Parkway
Canby, Oregon 97013
Tel: (888) 677-7776 (503) 266-2231
Fax: (503) 266-4334
www.srsmith.com



S.R. Smith LLC Commercial Division

Product Specifications - Written

Product Name: Pretzel Bend Handrails

Part Number: 10169 to 10174

General Notes:

The **Pretzel Bend Handrail** is a moderate height rail made of polished type 304 stainless steel.

Application:

The Pretzel Bend Handrail design allows the anchors to be placed laterally taking up a minimum amount of deck space. With proper anchoring, the Pretzel Bend Handrail is suitable for use on poured concrete, shotcrete, and fiberglass commercial pools and spas as well as for other applications in most geographic areas.

Specifications:

- 1 Handrail: The handrail is made of 1.90" O.D. (48.3 mm) type 304 polished stainless steel and is available in .109" or .145" (2.76mm, 3.68mm) wall thickness. All bends are a nominal 6" (152.4mm) radius.
- 2 Escutcheon (Optional): (p/n IEP-100): This recommended oblong escutcheon plate is 4" (101.6mm) in length and is made of chrome plated cast brass. The escutcheon includes a tamper resistant, stainless steel set screw. Alternative escutcheons include p/n EP-100A or EP-100F.
- 3 Anchor Assembly (Optional) (p/n IAS-100, see spec sheet for SRS-913): These recommended anchor sockets are bronze castings. They are intended for heavy-duty commercial use and secure fixtures by means of a wedge assembly. The anchor comes with a brass 1/4-20 UNC grounding screw for bonding. Alternative anchor assemblies include p/n AS-100B (see spec sheet for SRS-908).

Additional Product Numbers and Shipping Weight:

MODEL NUMBER	DESCRIPTION	SHIPPING WEIGHT
10169	Pretzel Bend Handrail 17" Setback 1.90" O.D. X .109" Wall	32 lbs. (14.5 kg.)
10170	Pretzel Bend Handrail 17" Setback 1.90" O.D. X .145" Wall	40 lbs. (18.2 kg.)
10171	Pretzel Bend Handrail 26" Setback 1.90" O.D. X .109" Wall	36 lbs. (16.3 kg.)
10172	Pretzel Bend Handrail 26" Setback 1.90" O.D. X .145" Wall	46 lbs. (20.9 kg.)
10173	Pretzel Bend Handrail 30" Setback 1.90" O.D. X .109" Wall	38 lbs. (17.3 kg.)
10174	Pretzel Bend Handrail 30" Setback 1.90" O.D. X .145" Wall	50 lbs. (22.7 kg.)

Specification Number:	SRS-612	
Product Description:	Pretzel Bend Handrail	
S.R. Smith Part Number:	10169 to 10174	
Revision:	A	Date: 07/29/03
Written By:	B. Svendsen	Date: 07/29/03
Approved By:	B. Bisceglia	Date: 07/29/03
Page 2 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.	

S.R. Smith, LLC
P.O. Box 400, 1017 SW Berg Parkway
Canby, Oregon 97013
Tel: (888) 677-7776 (503) 266-2231
Fax: (503) 266-4334
www.srsmith.com