


**Therapeutic Ladder**



SIDE VIEW

FRONT VIEW

MODEL NUMBER	A	B	(C)
TL-3B	39.00	12.00	70.00
TL-4C	49.00	14.50	80.00
TL-5D	59.00	17.00	90.00
TL-6E	69.00	19.50	100.00

NOTE: DEPENDING UPON THE DEPTH OF THE POOL AND THE LADDER MODEL CHOSEN, SOME ON-SITE ADJUSTMENT (CUTTING) OF THE (UPPER AND/OR LOWER) FRAME MAY BE NECESSARY TO INSURE PROPER SEATING OF THE LADDER ON THE POOL FLOOR.

Specification Number:	SRS-504		
Product Description:	Therapeutic Ladder		
S.R. Smith Part Number:	TL-3B to TL-6E	Scale:	NTS
Revision:	A	Date:	05/23/03
Written By:	T. Weil	Date:	05/23/03
Approved By:	B. Bisceglia	Date:	05/28/03
Page 1 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		

**S.R. Smith, LLC**  
P.O. Box 400, 1017 SW Berg Parkway  
Canby, Oregon 97013  
Tel: (888) 677-7776 (503) 266-2231  
Fax: (503) 266-4334  
www.srsmith.com



# S.R. Smith LLC Commercial Division

## Product Specifications - Written

**Product Name:** Therapeutic Ladder

**Part Number:** TL-3B to TL-6E

**General Notes:**

The **Therapeutic Ladder** is a tall height, long reach ladder with additional railing support for added security. This ladder can be used on both commercial and residential pools. The frame and steps are polished type 304 stainless steel. The ladder is available in 3, 4, 5, or 6 steps.

**Application:**

With proper anchoring, the Therapeutic Ladder is suitable for use on poured concrete or shotcrete pools in most geographic areas.

**Specifications:**

- 1 **Frame:** The frames are made of 1.9" O.D. x .065 (48.3mm x 1.65) type 304 stainless steel and all bends are a nominal 6" (152.4mm) radius. The lower ends of the frames have rubber bumper inserts, and rest on the pool floor. NOTE: Some cutting of the ladder may be required to insure a proper fit with the pool floor.
- 2 **Steps:** The steps are constructed of polished 304 stainless steel with nominal dimensions of 3" x 20 (76.2mm x 508). The step frames have replaceable, black, non-skid tread inserts.
- 3 **Escutcheon (Optional)** (p/n IEP-100): This recommended oblong escutcheon plate is 4" (101.6mm) in length and is made of chrome plated cast brass. The escutcheon includes a tamper resistant, stainless steel set screw. Alternative escutcheons include p/n EP-100A or EP-100F.
- 4 **Anchor Assembly** (p/n IAS-100, see spec sheet for SRS-913): These recommended anchor sockets are bronze castings. They are intended for heavy-duty commercial use and secure fixtures by means of a wedge assembly. The anchor comes with a brass 1/4-20 UNC grounding screw for bonding. Alternative anchor assemblies include p/n AS-100B (see spec sheet for SRS-908).

**Additional Product Numbers and Shipping Weight:**

Model Number	Description	Shipping Weight
TL-3B	3-Step Ladder	35 lbs. (15.9kg)
TL-4C	4-Step Ladder	41 lbs. (18.6kg)
TL-5D	5-Step Ladder	47 lbs. (21.3kg)
TL-6E	6-Step Ladder	55 lbs. (24.9kg)

Specification Number:	<b>SRS-504</b>	
Product Description:	<b>Therapeutic Ladder</b>	
S.R. Smith Part Number:	<b>TL-3B to TL-6E</b>	
Revision:	A	Date: 05/23/03
Written By:	T. Weil	Date: 05/23/03
Approved By:	B. Bisceglia	Date: 05/28/03
Page 2 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.	

**S.R. Smith, LLC**  
**P.O. Box 400, 1017 SW Berg Parkway**  
**Canby, Oregon 97013**  
**Tel: (888) 677-7776 (503) 266-2231**  
**Fax: (503) 266-4334**  
**www.srsmith.com**